

HD CAMERA

eco HD II - HIGH DEFINITION CAMERA

-
- Full HD resolution
 - High speed shutter
 - 8 endoscope presets available
 - Multilingual menu
-



HD CAMERA

eco HD II - HIGH DEFINITION CAMERA

Technical Data

Camera head:	<ul style="list-style-type: none">• Aspect ratio: 16:9• Image sensor: 1/2" CMOS				
Voltage range (current consumption):	<ul style="list-style-type: none">• 100-240 V				
Frequency:	<ul style="list-style-type: none">• 50-60 Hz				
Device protection:	<ul style="list-style-type: none">• 2x T3,15 A				
Video system:	<ul style="list-style-type: none">• Image resolution: full HD 1920 x 1080 (1080p)• TV resolution: > 900 lines• Sensitivity: < 3 lux (1/1.4)• White balance automatically, with data hold				
Connections	<table><tr><td>Video out terminal:</td><td>Other connections:</td></tr><tr><td><ul style="list-style-type: none">• 1x HDMI• 1x DVI• 1x SDI• 1x VIDEO</td><td><ul style="list-style-type: none">• 1 x USB (A) (Service)• 1 x Remote IN (footswitch)• 1 x RJ45 (Service)</td></tr></table>	Video out terminal:	Other connections:	<ul style="list-style-type: none">• 1x HDMI• 1x DVI• 1x SDI• 1x VIDEO	<ul style="list-style-type: none">• 1 x USB (A) (Service)• 1 x Remote IN (footswitch)• 1 x RJ45 (Service)
Video out terminal:	Other connections:				
<ul style="list-style-type: none">• 1x HDMI• 1x DVI• 1x SDI• 1x VIDEO	<ul style="list-style-type: none">• 1 x USB (A) (Service)• 1 x Remote IN (footswitch)• 1 x RJ45 (Service)				
Recording	<ul style="list-style-type: none">• Image format: JPG 1920 x 1080• Video format: Full HD 1920 x 1080• Connection: Front USB (A)				
Protection class (acc.to IEC 60601-1):	<ul style="list-style-type: none">• I				
Safety class:	<ul style="list-style-type: none">• BF				
IP code:	<ul style="list-style-type: none">• 20				
Standard:	<ul style="list-style-type: none">• IEC 60601-1-2				
Device classification (EU) 2017/745, annex VIII:	<ul style="list-style-type: none">• I				
Features:	<table><tr><td><ul style="list-style-type: none">• White balance• On-screen-menu• 8 endoscope presets</td><td><ul style="list-style-type: none">• Digital zoom• Freeze function</td></tr></table>	<ul style="list-style-type: none">• White balance• On-screen-menu• 8 endoscope presets	<ul style="list-style-type: none">• Digital zoom• Freeze function		
<ul style="list-style-type: none">• White balance• On-screen-menu• 8 endoscope presets	<ul style="list-style-type: none">• Digital zoom• Freeze function				
Dimensions (WxHxD):	<ul style="list-style-type: none">• 360mm x 125mm x 351mm				
Weight:	<ul style="list-style-type: none">• approx.4,5 kg				
Delivery contains:	<ul style="list-style-type: none">• CCU, camera head with 3,05m (10ft) cable, mains cable, HDMI - DVI cable, HDMI cable, user manual				

Options

Optional accessories:	<ul style="list-style-type: none">• Footswitch
-----------------------	--

Camera head with push buttons



Weight: approx. 180 g
Size: d= 38mm; l= 79mm
(without cable bend relief)