

HD CAMERA

eco HD - HIGH DEFINITION CAMERA

-
- Full HD resolution
 - High speed shutter
 - Multilingual menu
 - 10 user setting storable
-



HD CAMERA

eco HD - HIGH DEFINITION CAMERA

Technical Data

| | | | | | | | | | | | |
|--|--|---------------------------------|--------------------|------------------|------------------------------|-----------------------------|------------------------------|--|------------------|--|----------------------|
| Camera head: | <ul style="list-style-type: none">• Aspect ratio: 16:9• Image sensor: 1/3" CMOS• Immersible (using the attached cap) | | | | | | | | | | |
| Voltage range (current consumption): | • 100-240 V (25 VA) | | | | | | | | | | |
| Frequency: | • 50-60 Hz | | | | | | | | | | |
| Device protection: | • 2x T3,15 A | | | | | | | | | | |
| Video system: | <ul style="list-style-type: none">• Image resolution: full HD 1920 x 1080 (1080p)• TV resolution: > 900 lines• Sensitivity: < 3 lux (1/1.4)• White balance automatically, with data holdshutter speed: 1/50 (1/60) to 1/10.000 sec | | | | | | | | | | |
| Connections | <table><tr><td>Video out terminal:</td><td>Other connections:</td></tr><tr><td>• 1x HDMI</td><td>• 1 x USB (A) (USB-keyboard)</td></tr><tr><td></td><td>• 1 x Remote IN (footswitch)</td></tr><tr><td></td><td>• 2 x Remote OUT</td></tr><tr><td></td><td>• 2 x RJ45 (Service)</td></tr></table> | Video out terminal: | Other connections: | • 1x HDMI | • 1 x USB (A) (USB-keyboard) | | • 1 x Remote IN (footswitch) | | • 2 x Remote OUT | | • 2 x RJ45 (Service) |
| Video out terminal: | Other connections: | | | | | | | | | | |
| • 1x HDMI | • 1 x USB (A) (USB-keyboard) | | | | | | | | | | |
| | • 1 x Remote IN (footswitch) | | | | | | | | | | |
| | • 2 x Remote OUT | | | | | | | | | | |
| | • 2 x RJ45 (Service) | | | | | | | | | | |
| Protection class (acc.to IEC 60601-1): | • I | | | | | | | | | | |
| Safety class: | • BF | | | | | | | | | | |
| IP code: | • 20 | | | | | | | | | | |
| Standard: | • IEC 60601-1-2 | | | | | | | | | | |
| Device classification (EU) 2017/745, annex VIII: | • I | | | | | | | | | | |
| Features: | <table><tr><td>• White balance, boost function</td><td>• 2.5 digital zoom</td></tr><tr><td>• On-screen-menu</td><td>• Freeze function</td></tr><tr><td>• 10 user settings storable</td><td>• Character generator</td></tr></table> | • White balance, boost function | • 2.5 digital zoom | • On-screen-menu | • Freeze function | • 10 user settings storable | • Character generator | | | | |
| • White balance, boost function | • 2.5 digital zoom | | | | | | | | | | |
| • On-screen-menu | • Freeze function | | | | | | | | | | |
| • 10 user settings storable | • Character generator | | | | | | | | | | |
| Dimensions (WxHxD): | • 360mm x 125mm x 351mm | | | | | | | | | | |
| Weight: | • approx.4,7 kg | | | | | | | | | | |
| Delivery contains: | • CCU, camera head with 3,05m (10ft) cable, mains cable, HDMI - DVI cable, HDMI cable, user manual | | | | | | | | | | |

Options

| | | |
|-----------------------|-----------------------|--------------|
| Optional accessories: | • Waterproof keyboard | • Footswitch |
|-----------------------|-----------------------|--------------|

Camera head without push buttons



Weight: approx. 150g
Size: d= 36,5mm; l= 65mm
(without bending sleeve)

Camera head with push buttons



Weight: approx. 180 g
Size: d= 38mm; l= 79mm
(without bending sleeve)