

LIGHTSOURCE

LED 1800 / LED 2500 - HIGH INTENSITY LIGHTSOURCE

-
- Low noise, low heat conduction
 - Electronical light control via buttons
 - Pure daylight quality
-



LIGHTSOURCE

LED 1800 / LED 2500 - HIGH INTENSITY LIGHTSOURCE

Series

Description

LED 1800 / 2500

Storz adapter, automatic light intensity control

Technical Data

LED module:

LED 2500:

- LED CRI 70, Daylight quality, approx. 6500 K
- Lifetime: > 20.000 hr

LED 1800:

- LED CRI 90, Daylight quality, approx. 5700 K
- Lifetime: > 20.000 hr

Light guide connection:

- Storz, Wolf

Voltage range (current consumption):

- 100-240 V (130 VA)

Frequency:

- 50-60 Hz

Device protection:

- 2x T3,15 A

Video In:

- 1x Video, BNC

Other connections:

- Service (RJ45)

Protection class (acc.to IEC 60601-1):

- I

Safety class:

- BF

IP code:

- 20

Standard:

- IEC 60601-1-2

Device classification (acc. to MDD 93/42/EEC):

- I

Dimensions (WxHxD):

- (WxHxD) 360 x 124 x 335 mm

Weight:

- approx. 5 kg

Delivery contains:

- Light source, mains cable, user manual, BNC cable (optional)