


LIGHTSOURCE

LED 2500 - HIGH INTENSITY LIGHTSOURCE

-
- Low noise, low heat conduction
 - Electronical light control via buttons
 - Pure daylight quality
-



LIGHTSOURCE

LED 2500 - HIGH INTENSITY LIGHTSOURCE

Series	Description
LED 2500	Storz adapter, automatic light intensity control

Technical Data

LED module:	LED 2500: <ul style="list-style-type: none">• LED CRI 70, Daylight quality, approx. 6500 K• Lifetime: > 20.000 hr
Light guide connection:	• Storz, Wolf
Voltage range (current consumption):	• 100-240 V (130 VA)
Frequency:	• 50-60 Hz
Device protection:	• 2x T3,15 A
Video In:	• 1x Video, BNC
Other connections:	• Service (RJ45)
Protection class (acc.to IEC 60601-1):	• I
Safety class:	• BF
IP code:	• 20
Standard:	• IEC 60601-1-2
Device classification (EU) 2017/745, annex VIII:	• I
Dimensions (WxHxD):	• (WxHxD) 360 x 125 x 351 mm
Weight:	• approx. 5 kg
Delivery contains:	• Light source, mains cable, user manual, BNC cable (optional)

IMPORTANT:

Use only high-performance light cables / high-temperature-resistant light guides!