

## LIGHT SOURCE

### XENON LIGHT SOURCE 300W

- Low noise, low heat conduction
- Electronical light control via buttons
- Simple lamp replacement
- Waterproof touch control panel



# LIGHT SOURCE

## XENON LIGHT SOURCE 300W

Series	Description
<b>Single Version:</b>	
Xenon X 300-M	300 Watt xenon lamp, Storz adapter, manual light intensity control
Xenon X 300-A	300 Watt xenon lamp, Storz adapter, automatic light intensity control
Xenon X 300-AT	300 Watt xenon lamp, turret adapter, automatic light intensity control
<b>Backup version:</b>	
Xenon X300M-LED	300 Watt xenon lamp, Backup LED lamp, 2x Storz adapter manual light intensity control
Xenon X300A-LED	300 Watt xenon lamp, Backup LED lamp, 2x Storz adapter automatic light intensity control
Xenon X300AT-LED	300 Watt xenon lamp, Backup LED lamp, 2x turret adapter automatic light intensity control

### Technical Data

Lamp:	Main: <ul style="list-style-type: none"><li>• Xenon arc lamp: 300 W</li><li>• Daylight quality, 5600 K</li><li>• Lifetime: 500 hr (expected)</li></ul> Backup (optional): <ul style="list-style-type: none"><li>• White LED lamp</li><li>• Daylight quality, 6500 K</li><li>• Lifetime: &gt; 20.000 hr</li></ul>
Light guide connection:	• Storz, Wolf, Olympus or turret adapter
Voltage range (current consumption):	• 100-240 V (300W light source: 370 VA)
Frequency:	• 50-60 Hz
Device protection:	• 2x T6,3 A
Video In (optional):	• 1x Video (automatic Version only)
Protection class (acc.to IEC 60601-1):	• I
Safety class:	• BF
IP code:	• 20
Standard:	• IEC 60601-1-2
Device classification (EU) 2017/745, annex VIII:	• I
Dimensions (WxHxD):	• 355mm x 120mm x 340mm
Weight:	• approx. 12,5 kg (300W)
Delivery contains:	• Light source, mains cable, user manual, BNC cable (optional)
Options:	• Automatic light intensity control • Backup LED lamp • Multi connector option, turret:

Wolf



ACMI



Olympus



Storz

Ø max. 5,9mm



min. 4mm

Exclusively pictured version!